

WARNINGS

MAKE NO ATTEMPT TO PUT THE AMPLIFIER IN SERVICE OUTSIDE OF THE CABINET. CONTACT WITH HIGH VOLTAGES FOUND IN THE AMPLIFIER CAN BE FATAL.

NEVER OPERATE ANY AMPLIFIER FROM AN EXTENSION CORD.

COMPLETELY REMOVE POWER FROM YOUR AMPLIFIER AND ALLOW 30 MINUTES FOR THE HIGH VOLTAGE CAPACITORS TO DISCHARGE THROUGH BLEEDER RESISTORS BEFORE ATTEMPTING TO CHANGE JUMPER CONNECTIONS IN BACK OF AMPLIFIER.

CAUTIONS

NEVER REMOVE/INSERT PLUG WHEN UNIT IS ON OR WHEN THE RF DECK AC LINE CORD IS CONNECTED TO AN AC POWER SOURCE.

ENSURE TUBES ARE INSTALLED PRIOR TO APPLYING POWER TO THE AMPLIFIER.

OBSTRUCTION OF THE SIDES OF THE AMPLIFIER/CASE AND THE BLOWER AIR INLET MAY RESULT IN AMPLIFIER TUBE(S) OVERHEATING.

THE UNIT IS SHIPPED READY FOR 234VAC OPERATION. REFER TO INSTALLATION INSTRUCTIONS FOR 117V OPERATION.

OBSERVE CURRENT LIMITATIONS FOR NORMAL OPERATION.

DO NOT BLOW AIR DIRECTLY INTO FAN BLADES. USE A BRUSH FOR CLEANING THE BLADES.